

***Model Number**

EUROPALAMP-10-165
Power: 10W
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 810LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/6000K
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 10W LED = 80W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 155*110*30mm
 30PCS/CTN G.W.: 13.7KGS/CTN Carton Size: 51.5*27.5*24.5cm



***Model Number**

EUROPALAMP 10-165S
Power: 10W PIR
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 810LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/6000K
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 10W LED = 80W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 155*167*55mm
 30PCS/CTN G.W.: 16.6KGS/CTN Carton Size: 51.5*34.5*36.5cm



***Model Number**

EUROPALAMP-20-165
Power: 20W
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 1660LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/6000K
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 20W LED = 160W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 155*110*30mm
 30PCS/CTN G.W.: 13.8KGS/CTN Carton Size: 51.5*27.5*24.5cm



***Model Number**

EUROPALAMP-20-165S
Power: 20W PIR
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 1660LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/6000K
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 20W LED = 160W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 155*167*55mm
 30PCS/CTN G.W.: 16.6KGS/CTN Carton Size: 51.5*34.5*36.5cm



***Model Number**

Power: 30W
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 2480LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/6000K
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 30W LED = 240W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 230*150*35mm



***Model Number**

Power: 30W PIR
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 2480LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/6000K
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 30W LED = 240W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 230*215*55mm



***Model Number**

Power: 50W
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 4250LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/6000K
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 50W LED = 400W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 280*180*50mm



***Model Number**

Power: 50W PIR
 Input Voltage: AC90-265V
 Frequency: 50-60 Hz
 Luminous Flux: 4250LM
 Color of the shell: grey
 Color Temperature: 3000K/4500K/
 Life-span:>50000 Hours
 Beam Angle: 120°
 Dimmable: Non
 EU Energy Efficiency Label: A
 Working temperature:-40° to +65°C
 50W LED = 400W incandescent lamp
 Material: Aluminum+tempered glass
 CRI>75 Ra
 LED Chips: Epistar 5730SMD
 IP rate: IP65
 Warranty: 2 years
 Certificates: CE, RoHS, ISO9001
 Product Size: 280*235*60mm



***Model Number**

Power: 100W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Flux: 8190LM
Color of the shell: grey
Color Temperature: 3000K/4500K/6000K
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
100W LED = 800W incandescent lamp
Material: Aluminum+tempered glass
CRI>75 Ra
LED Chips: Epistar 5730SMD
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 330*220*60mm



***Model Number**

Power: 150W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Flux: 12750LM
Color of the shell: grey
Color Temperature: 3000K/4500K/6000K
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
150W LED = 300W halogen lamp
Material: Aluminum+tempered glass
CRI>75 Ra
LED Chips: Epistar 5730SMD
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 390*288*170mm



***Model Number**

Power: 200W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Flux: 18800LM
Color of the shell: grey
Color Temperature: 3000K/4500K/6000K
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
200W LED = 1200W halogen lamp
Material: Aluminum+tempered glass
CRI>75 Ra
LED Chips: Epistar 5730SMD
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 370*370*120mm



***Model Number**

Power: 400W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Flux: 34200LM
Color of the shell: grey
Color Temperature: 3000K/4500K/6000K
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
400W LED = 2400W metal halogen lamp
Material: Aluminum+tempered glass
CRI>75 Ra
LED Chips: Epistar 5730SMD
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 430*385*120mm



***Model Number**

Power: 10W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Efficiency: 85-90LM/W
Color of the shell: grey
Emitting Color: RGB
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
Material: Aluminum+tempered glass
With remote controller: yes
LED Chips: Epistar COB
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 125*115*35mm



***Model Number**

Power: 20W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Efficiency: 85-90LM/W
Color of the shell: grey
Emitting Color: RGB
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
Material: Aluminum+tempered glass
CRI>75 Ra
LED Chips: Epistar COB
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 178*135*43mm



***Model Number**

Power: 30W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Efficiency: 85-90LM/W
Color of the shell: grey
Emitting Color: RGB
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
Material: Aluminum+tempered glass
With remote controller: yes
LED Chips: Epistar COB
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 223*175*46mm



***Model Number**

Power: 50W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Efficiency: 85-90LM/W
Color of the shell: grey
Emitting Color: RGB
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
Material: Aluminum+tempered glass
CRI>75 Ra
LED Chips: Epistar COB
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 280*230*54mm



***Model Number**

Power: 100W

Input Voltage: AC90-265V
Frequency: 50-60 Hz
Luminous Efficiency: 85-90LM/W
Color of the shell: grey
Emitting Color: RGB
Life-span:>50000 Hours
Beam Angle: 120°
Dimmable: Non
EU Energy Efficiency Label: A
Working temperature:-40° to +65°C
Material: Aluminum+tempered glass
With remote controller: yes
LED Chips: Epistar COB
IP rate: IP65
Warranty: 2 years
Certificates: CE, RoHS, ISO9001
Product Size: 285*335*70mm





Color Temperature Shown

There are 3 color temperatures available, as below:

